

**REPORT DOCUMENTATION PAGE**Form Approved  
OMB NO. 0704-0188

Public Reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comment regarding this burden estimates or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188,) Washington, DC 20503.

1. AGENCY USE ONLY (Leave Blank)		2. REPORT DATE 6/30/98		3. REPORT TYPE AND DATES COVERED Annual Performance: 7/1/97-6/30/98	
4. TITLE AND SUBTITLE Nonlinear Circuits and Neural Networks: Chip Implementation and Applications of the TeraOPS CNN Dynamic Array Supercomputer				5. FUNDING NUMBERS  N00014-98-1-0052	
6. AUTHOR(S)  L. Chua					
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) University of California, Berkeley, CA 94720				8. PERFORMING ORGANIZATION REPORT NUMBER 442427-23051	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) Office of Naval Research / ONR 311 Ballston Centre Tower One 800 North Quincy Street Arlington, VA 22217-5660				10. SPONSORING / MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES N/A					
12 a. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release; distribution unlimited.				12 b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words)  During the period July 1997 – June 1998 work has continued according to the proposed plan. Advances in research have been made in the following areas: <ul style="list-style-type: none"><li>• The design and implementation of the first-ever ARAM in the CNN Chip Set Architecture was successfully competed, and the samples were successfully tested;</li><li>• A major theoretical breakthrough has been achieved: it was shown that the genesis of complexity lies in the local activity of the cells and local interactions of the Cellular Nonlinear Networks;</li><li>• Several CNN templates and subroutine designs, including mathematical morphology, have been developed and used in various applications;</li><li>• Advances in application of CNN have been made in the area of condition-based maintenance and image fusion.</li></ul>					
14. SUBJECT TERMS				15. NUMBER OF PAGES 5	
				16. PRICE CODE	
17. SECURITY CLASSIFICATION OR REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION ON THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT  UL		

NSN 7540-01-280-5500

Form 298 (Rev.2-89)

Prescribed by ANSI Std. Z39-18

Standard

19980710 138

**PROGRESS REPORT**

*for the period July 1997 -June 1998, on*

***Nonlinear Circuits and Neural Networks:  
Chip Implementation and Applications of the TeraOPS CNN  
Dynamic Array Supercomputer  
Grant No. N00014-98-1-0052  
1996-1998***

*L. O. Chua*

*Principal Investigator*

*Nonlinear Electronics Laboratory*

*University of California, Berkeley*

---

## Summary

---

During the period July 1997 - June 1998, our work has been continued according to the proposed plan. Advances in research have been made in the following areas:

- The design and implementation of the first-ever ARAM in the CNN Chip Set Architecture was successfully completed, the samples were successfully tested;
- A major theoretical breakthrough has been achieved: it was shown that the genesis of complexity lies in the local activity of the cells and local interactions of the Cellular Nonlinear Networks; in addition
- Several CNN templates and subroutine designs, including mathematical morphology, have been developed and used in various applications;
- Advances in application of CNN have been made in the area of condition based maintenance and image fusion.

**Task 1:** *The design and implementation of the first-ever ARAM in the CNN Chip Set Architecture, measurements of the operational CNN Universal Chips*

An analog random-access memory chip (ARAM) in a 32x256 configuration has been designed and fabricated through the MOSIS service using Hewlett-Packard's 0.5-micron CMOS technology. The main parameters of the ARAM chip are as follows:

- 637 analog memory cells/mm<sup>2</sup>,
- 7-8 bits of accuracy,
- 10 MS/sec input rate 1MS/sec output rate,
- 80-100 msec storage time.

The innovative circuit design solutions provide for robust operation. A series of electrical tests at our laboratory in Berkeley confirmed the design goals. Functional tests executed in Budapest in the framework of an ONR - NICOP grant, showed that the

specified accuracy is enough to produce practically distortionless images when viewed by a human observer.

**Task 2: *The local activity principle***

Complex systems that consist of a very large number of nonlinear dynamical systems distributed in space and having local interconnections, exhibit emergent, self-organizing, and sometimes exotic properties in space and time. Although these truly interdisciplinary phenomena have been widely studied and described, no solid and rigorous conditions have been established for explaining the genesis of these systems and why they exhibit the surprising or strange phenomena.

It has been shown that the principle of local activity is the key to explaining these unusual properties. In addition, analytical tools have been developed to determine the parameter ranges for exploiting the local activity conditions and to construct useful systems.

**Task 3: *Design of new templates and subroutines, including mathematical morphology***

Innovative applications, like condition based maintenance and image fusion, need new templates and subroutines, especially for the spatial-temporal kind of processing where CNN technology truly excels. Mathematical-morphology based tools are very attractive for the algorithm designer and provide a powerful tool for solving a large set of difficult problems. Their implementation, however, in classical computers is inefficient. CNN computing technology provides for a natural platform for mathematical morphology. Several templates and subroutines have been developed and used in the applications described below. An important result is the implementation of a wave-type metric.

#### **Task 4. *Application case studies.***

Condition based maintenance for detecting the start of deterioration in helicopter engines is an ambitious task for today's technology. Teaming up with Dr. Abe Schultz at the Naval Research Laboratory, we have developed analogic CNN algorithms to solve both the basic image preprocessing and also the subsequent classification task to detect debris particles in the high-speed oil flow of a helicopter gear-box. A major difficulty in solving this problem is the presence of a large number of air bubbles in the flow.

Preprocessing algorithms have also been developed for image fusion.

#### **References**

- [1.] R. Carmona, S. Espejo, R. Dominguez-Castro, A. Rodriguez-Vazquez, T. Roska, T. Kozek, and L. O. Chua, "A 0.5um CMOS CNN Analog Random Access Memory Chip for Massive Image Processing" in Proc. of the 5th Int. Workshop on Cellular Neural Networks and its Applications, pp. 271-276, London, UK, April 1998.
- [2.] R. Carmona, S. Espejo, R. Dominguez-Castro, A. Rodriguez-Vazquez, T. Roska, T. Kozek, and L. O. Chua, "A 0.5um CMOS Random Access Analog Memory Chip for High Speed Analog Computing," IEEE Transactions on Circuits and Systems-I, Special Issue on Bio-inspired Processors and CNNs for Vision, (Submitted for publication)
- [3.] A. Schultz, Cs. Rekeczky, I. Szatmari, T. Roska, T. Kozek, and L. O. Chua, "Spatio-temporal CNN algorithm for object segmentation and object recognition," in Proc. of the 5th Int. Workshop on Cellular Neural Networks and its Applications, pp. 347-352, London, UK, April 1998.
- [4.] Gilli, M.; Civalleri, P.P.; Roska, T.; Chua, L.O. Chua, "Analysis of time-varying cellular neural networks for quadratic global optimization. International Journal of Circuit Theory and Applications, March-April 1998, vol.26, (no.2):109-26.
- [5.] Zarandy, A.; Stoffels, A.; Roska, T.; Chua, L.O. Chua "Implementation of binary and gray-scale mathematical morphology on the CNN universal machine," IEEE Transactions on Circuits and Systems I: Fundamental Theory and Applications, Feb. 1998, vol.45, (no.2):163-8.
- [6.] Cruz, J.M.; Chua, L.O. Chua, "A 16\*16 cellular neural network universal chip: the first complete single-chip dynamic computer array with distributed memory and with gray-scale input-output," Analog Integrated Circuits and Signal Processing, March 1998, vol.15, (no.3):227-37.

- [7.] Kozek, T.; Chai Wah Wu; Zarandy, A.; Hua Chen; and others," New results and measurements related to some tasks in object-oriented dynamic image coding using CNN universal chips," IEEE Transactions on Circuits and Systems for Video Technology, Aug. 1997, vol.7, (no.4):606-14.
- [8.] Takahashi, N.; Chua, L.O. Chua, "A new sufficient condition for nonsymmetric CNNs to have a stable equilibrium point," IEEE Transactions on Circuits and Systems I: Fundamental Theory and Applications, Nov. 1997, vol.44, (no.11):1092-5.
- [9.] Stoffels, A.; Roska, T.; Chua, L.O. Chua, "Object-oriented image analysis for very-low-bitrate video-coding systems using the CNN universal machine," International Journal of Circuit Theory and Applications, July-Aug. 1997, vol.25, (no.4):235-58.
- [10.] Crounse, K.R.; Fung, E.L.; Chua, L.O. Chua, "Efficient implementation of neighborhood logic for cellular automata via the Cellular Neural Network Universal Machine," IEEE Transactions on Circuits and Systems I: Fundamental Theory and Applications, April 1997, vol.44, (no.4):355-61.
- [11.] Chai Wah Wu; Chua, L.O. Chua, "A more rigorous proof of complete stability of cellular neural networks," IEEE Transactions on Circuits and Systems I: Fundamental Theory and Applications, April 1997, vol.44, (no.4):370-1.